

# PolyWipes IG (Industrial Grade)

## Technical Data Sheet

## **Description**

PolyWipes are a unique non-woven fabric impregnated with a non-toxic aqueous solution designed to safely remove uncured or partly cured adhesives, sealants, including polysulfide and silicone, greases, oils, and other contaminates. PolyWipes proprietary aqueous formulation is designed to reduce surface tension between the material and the substrate. Once reduced, the wipe picks up the material from the substrate for easy disposal. Since PolyWipes are non-toxic they eliminate the need to use hazardous solvents in the worlplace.

## <u>Advantages</u>

- Non-toxic
- Non-flammable
- Non-hazardous Not subject to dangerous goods regulations.
- No phosphates, acids or silicones
- Neutral pH of 6-7
- Fresh smell NOT citrus

## Application

PolyWipes are intended for use at room temperature (68°F-80°F). They can be used to clean up after applying sealant in numerous industries:

- Marine to clean up after applying adhesives in the construction of fiberglass watercraft and during repair.
- Construction to clean any excess caulking or sealant from windows, doors, bathrooms and kitchens.
- Manufacturers using adhesives or sealants to remove excess uncured adhesives or sealants in manufacturing and assembly processes.
- Machine Shop to remove drilling oils, grease, and other contaminates from finished parts.

## Directions for Use

Remove wipe from container and fully open the wipe. Place wipe over sealant to be "picked up". Use one hand and press down on the suface next to the sealant. Rotate hand and flick the material off the surface. Fold the towelette on itself and continue until the sealant is removed. Dispose of towel when finished.

## Package Sizes

150-wipe poly containers4 x 150-wipe poly container cases

Shelf Life

2-years

### Storage

Do not store under 35°F/2C and not above 122°F/50C. Do not use below 35°F/2C.

#### Properties

NFPA Hazard Class:	Health	0
	Flammability	0
	Reactivity	0

VOC:Not testedpH:>6 < 7</td>Flash point:N.A.

 $\label{eq:RPM_technology} RPM Technology, LLC \cdot 973-463-1386 \cdot \underline{sales@rpm-technology.com} \cdot \underline{www.rpm-technology.com}$ 

Disclaimer: RPM Technology, LLC believes the information contained herein is accurate; however, makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein by any party. The provision of the information contained herein and the provision of information by or reliance on RPM Technology, LLC Technical and Environmental Services Department is not intended to be and should not be construed as legal advice or as ensuring compliance with any country, federal, state, or local laws and regulations.