



eOx[®] Industrial
Made in the USA

Technical Data Sheet

Description

eOx Industrial is a powerful general purpose cleaner with a broad range of applications that require light corrosion protection. It is a replacement for organic solvents (aliphatic hydrocarbons, white spirits, thinner, etc.), chlorinated products and solvent/emulsion cleaners. eOx Industrial removes all kinds of oil, grease and dirt from surfaces without effort. Its performance surpasses other alkaline cleaning agents due to its faster and more intensive action. eOx Industrial removes unpleasant odors and has a fresh smell. eOx leaves the cleaned surface antistatic which helps the surface stay clean longer. It is specially designed to meet stronger local legislations, is solvent free, human and wastewater friendly. Although this product has a high pH (12.8), which gives it an excellent and strong cleaning effect, it does not affect metals; including aluminium as it is inhibited for this use.

Advantages

- Non-toxic
- Non-flammable
- Non-hazardous - Not subject to dangerous goods regulations.
- No phosphates, acids or silicones and is non-butyl.
- Very economical to use.
- Fast, intense cleaning action surpasses other cleaners' performance.
- Cleaned surfaces become slightly antistatic and corrosion inhibitive for up to 4 weeks.
- Can be effectively used as a spray-on & wipe-off process.
- Safe for use in high-pressure washers, immersion systems and ultrasonic machines.
- High biodegradability (tested by the University of Ghent, Belgium)
- Quickly de-emulsifies, resulting in excellent oil and water separation
- Fresh smell – NOT citrus
- Safe to use on all metals, plastics, lacquer paints, floors, walls, ceilings, etc

Application

eOx Industrial may be safely used in cleaning fountains, immersion or ultrasonic baths, parts washers, high-pressure cleaners, and other industrial cleaning machines. It is an ideal product when a corrosion inhibitor is needed to prevent corrosion onset for up to ±7 days.

Directions for Use

- Whatever system is used for cleaning with eOx Industrial, a mechanical action (brush, sponge, aeration of solution, ultrasonic, etc.) is required to break the surface tension of the dirt. Just soaking for an extended time will not be sufficient for cleaning.
- eOx Industrial is not flammable and can be safely heated. For immersion or ultrasonic baths we recommend 50° C/122° F to minimize the evaporation rate.
- eOx Industrial is highly concentrated. If the product is not sufficiently diluted, a white haze or stripes can be left after drying especially on very smooth or shiny surfaces. This haze will disappear when the surface is treated again with the correct dilution.

- Rinsing all parts, pipes and surfaces is important so no residue remains. Rinsing with warm water is not necessary but will enhance the drying process. If needed, use compressed air to speed up drying time.
- eOx Industrial can be used in a "final cleaning" process to gain the corrosion inhibitive property after using another eOx product.

Spray the surface to be cleaned with eOx Industrial, brush in, allow a short time for the product to work in (10 seconds), remove dirt by brush. Let it dry. When the cleaned item is to be painted, rinse with plenty water or use eOx Economic at a 1:50 dilution. Anti-foam formulations are available if needed.

Package Sizes

1-gallon poly bottles
4 x 1-gallon cases
55-gallon poly drums

Shelf Life

4-years

Storage

Do not store under 35°F/2C and not above 122°F/50C. Do not use below 35°F/2C.

Properties

NFPA Hazard Class:	Health	0 (as used)
	Flammability	0
	Reactivity	0

VOC: < 1 g/L (as used)
pH: 12.9 (concentrate)
Flash point: None

RPM Technology, LLC · 973-463-1386 · sales@rpm-technology.com · www.rpm-technology.com

Disclaimer: RPM Technology, LLC believes the information contained herein is accurate; however, makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein by any party. The provision of the information contained herein and the provision of information by or reliance on RPM Technology, LLC Technical and Environmental Services Department is not intended to be and should not be construed as legal advice or as ensuring compliance with any country, federal, state, or local laws and regulations.